



HAL
open science

Towards an efficient implementation of CADNA in the BLAS : Example of DgemmCADNA routine.

Séthy Montan, Jean-Marie Chesneaux, Christophe Denis, Jean-Luc Lamotte

► **To cite this version:**

Séthy Montan, Jean-Marie Chesneaux, Christophe Denis, Jean-Luc Lamotte. Towards an efficient implementation of CADNA in the BLAS : Example of DgemmCADNA routine.. 15th GAMM - IMACS International Symposium on Scientific Computing, Computer Arithmetic, and Validated Numerics (SCAN), Sep 2012, Novosibirsk, Russia. hal-00765529

HAL Id: hal-00765529

<https://hal.sorbonne-universite.fr/hal-00765529>

Submitted on 14 Dec 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Towards an efficient implementation of CADNA in the BLAS : Example of DgemmCADNA routine.

Sethy Montan^{1,*}, Jean-Marie Chesneaux^{*}, Christophe Denis¹,
Jean-Luc Lamotte^{*}.

¹ EDF R&D - Département SINETICS - 1, Avenue du général de Gaulle 92141
Clamart Cedex - France.

^{*} Laboratoire d'Informatique de Paris 6 - Université Pierre et Marie Curie, 4 place
Jussieu 75252 Paris Cedex 05 - France.
`sethy.montan@edf.fr`

Keywords: CADNA, Discret Stochastic arithmetic, CESTAC, BLAS.

Several approximations occur during a numerical simulation : physical phenomena are modelled using mathematical equations, continuous functions are replaced by discretized ones and real numbers are replaced by finite-precision representations (floating-point numbers). The use of the IEEE-754 arithmetic generates round-off errors at each elementary arithmetic operation. By accumulation, these errors can affect the accuracy of computed results, possibly leading to partial or total inaccuracy. The effect of these rounding errors can be analyzed and studied by some methods like forward/backward analysis, interval arithmetic or stochastic arithmetic (which is implemented in the CADNA validation tool).

A numerical verification of industrial codes, such those that are developed at EDF R&D –the French provider of electricity–, is required to estimate the precision and the quality of computed results, even more for code running in HPC environments where millions instructions are performed each second. These programs usually use external libraries (MPI, BLACS, BLAS, LAPACK) [1]. In this context, it is required to have a tool as nonintrusive as possible to avoid rewriting the original code. In this regard, the CADNA library appears to be one of the promising approach for industrial applications.

The CADNA library, developed by the Laboratoire d'Informatique de Paris 6, enables us to estimate round-off error propagation using a probabilistic approach in any simulation program (written in C/C++ or Fortran) and to control its numerical quality by detecting numerical instabilities that may occur at run time [2]. CADNA implements Discrete Stochastic Arithmetic which is based on a probabilistic model of round-off errors (this arithmetic is defined with the CESTAC Method). CADNA

provides new numerical types, the so-called stochastic types, on which round-off errors can be estimated. However, a problem remains: stochastic types are not compatible with the aforementioned libraries. It is, therefore, necessary to develop some extensions for these external libraries.

We are interested in an efficient implementation of the BLAS routine xGEMM compatible with CADNA. We have called this new routine *DgemmCADNA*. The BLAS (Basic Linear Algebra Subprograms) are routines that provide standard building blocks for performing basic vector and matrix operations and xGEMM is the routine which goal is to perform matrix multiplication [5]. The implementation of a basic algorithm for matrix product compatible with stochastic types leads to an overhead greater than 1000 for a matrix of 1024*1024 compared to the standard version and commercial versions of xGEMM. This overhead is due to the use of stochastic types, the rounding mode which changes randomly at each elementary operation (\times , $/$, $+$, $-$), and a non optimized use of the memory (cache and TLB misses).

We will present different solutions to reduce this overhead and the results we have obtained. In order to improve the hierarchical memory usage, special data structures (Block Data Layout) are used. This allows us to improve the memory performance to reduce cache and TLB misses. A new implementation of CESTAC Method has been introduced to reduce the overhead due to the random rounding mode. Finally, we have obtained an overhead about 25 compared to GotoBLAS in a sequential mode.

We will also present, briefly, new extensions for CADNA : CADNA_MPI and CADNA_BLACS which allow to use stochastic data in programs using the communications standard routines (MPI or BLACS).

References

- [1] Christophe Denis, and Séthy Montan, Numerical verification of industrial numerical codes, ESAIM Proceedings, volume 35, pages 107–113, March 2012.
- [2] Fabienne Jézéquel, Jean-Marie Chesneaux, and Jean-Luc Lamotte, A new version of the CADNA library for estimating round-off error propagation in Fortran programs, Computer Physics Communications, volume 181(11), pages 1927–1928, 2010.
- [3] K. Goto, and R.A. Van De Geijn, High-performance implementation of the level-3 BLAS, ACM Transactions on Mathematical Software (TOMS), volume 35 (1), pages 4, 2008.
- [4] N.J. Higham, Accuracy and Stability of Numerical Algorithms, 2nd ed., Society for Industrial and Applied Mathematics, Philadelphia, PA, USA, 2002.
- [5] Basic Linear Algebra Technical Forum, Basic Linear Algebra Technical Forum Standard, August 2001.