



**HAL**  
open science

# True link detection in the presence of per packet load balancers

Thomas Bourgeau, Timur Friedman

► **To cite this version:**

Thomas Bourgeau, Timur Friedman. True link detection in the presence of per packet load balancers. 11e Rencontres Francophones sur les aspects Algorithmiques des Télécommunications (ALGOTEL), Jun 2009, Carry-Le-Rouet, France. . hal-01500466

**HAL Id: hal-01500466**

**<https://hal.sorbonne-universite.fr/hal-01500466>**

Submitted on 3 Apr 2017

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## True link detection in the presence of per packet load balancers

Thomas Bourgeau and Timur Friedman

Mails : {thomas.bourgeau, timur.friedman}@lip6.fr

**Introduction:** Recent studies have shown that the traceroute tool does not provide reliable topological information when probing through load balancers [1]. Paris Traceroute was developed to correct this problem as it traces correct paths through per-flow load balancers (PFLBs) and per-destination load balancers (PDLs). However it is unable to do so for per-packet load balancer (PPLBs).

**Motivation:** We propose to enhance Paris Traceroute with a new algorithm to resolve true link detection with PPLBs. When cross traffic occurs we apply statistical tests in our algorithm. Enough PPLBs are found in network paths: Augustin et al. found that PPLBs appears in 2% of the traces obtained by a list of 60000 destinations

### Problem Description




Fig 1.a: Simple diamond topology

- Paris Traceroute with the MDA algorithm [2] obtains all the interfaces that are present in the underlying topology (Fig 1.a) when L is a PPLB.
- But any of the links in  $\{A, B, C\} \times \{D, E, F\}$  is possible (Fig 1.b), meaning that the true links (A, D), (B, E), and (C, F) are not explicitly detected due to the lack of an inference algorithm.




Fig 1.b: Possible inferred links

### Proposed Algorithm

Our algorithm determines the true links in a PPLB diamond in two main steps:

**Step 1:** Discovers the estimated round robin pattern at each multi interface hop in the diamond.

	PatternProbe	PatternAnalysis																
With No Cross Traffic	Sends $k_l$ probes to each multi interface hops in the diamond.	Estimate the Round Robin pattern at each hop.																
	<p>Fig 1.b: Pattern with no cross traffic</p> <p>With no cross traffic, the discovered interfaces follow a periodical cycle at each hop, which indicates that PPLBs follow a round robin pattern (Fig 1.b).</p>	Build the lateral count matrix $T_i$ with PatternProbe results: <table border="1"> <tr><th></th><th>A</th><th>B</th><th>C</th></tr> <tr><th>A</th><td>0</td><td>17</td><td>0</td></tr> <tr><th>B</th><td>0</td><td>0</td><td>17</td></tr> <tr><th>C</th><td>16</td><td>0</td><td>0</td></tr> </table> Estimate the Round Robin pattern: <ul style="list-style-type: none"> <li>• Search the argument of the maximum value found in each row of <math>T_i</math></li> <li>• Build an ordered cycle <math>G_i</math> with the argument value found in <math>T_i</math></li> </ul>		A	B	C	A	0	17	0	B	0	0	17	C	16	0	0
	A	B	C															
A	0	17	0															
B	0	0	17															
C	16	0	0															
With Cross Traffic																		
	<p>Fig 1.c: Pattern with cross traffic</p> <p>With cross traffic, the observation are disrupted as the discovered interfaces don't follow the underlying periodic cycle (Fig 1.c). We need to use statistical tests to uncover the round robin pattern.</p>	Build the lateral count matrix $T_i$ with PatternProbe results: <table border="1"> <tr><th></th><th>A</th><th>B</th><th>C</th></tr> <tr><th>A</th><td>4</td><td>9</td><td>3</td></tr> <tr><th>B</th><td>1</td><td>4</td><td>8</td></tr> <tr><th>C</th><td>11</td><td>6</td><td>6</td></tr> </table> Estimate the Round Robin pattern: <ul style="list-style-type: none"> <li>• Use a Binomial distribution to model the transition of each individual interfaces as a result of randomness</li> <li>• Reject each real transition that have a random behaviour by comparing them to the Binomial distribution results.</li> </ul>		A	B	C	A	4	9	3	B	1	4	8	C	11	6	6
	A	B	C															
A	4	9	3															
B	1	4	8															
C	11	6	6															

$$G_2 = (A, B, C)$$

$$G_3 = (D, E, F)$$

**Step 2:** Finds out how each hops pattern aligns with that of its neighbors.

	PairProbe	PatternAlignment																
	Sends $k_f$ back-to-back probes successively to two adjacent hops.	Estimates the alignments between the inferred round robin patterns																
With no cross traffic we know that our observation are not disrupted.	Need to send $k_f=1$ back-to-back probe to find one correct forward transition.	Build the forward transition matrix $M_i$ with PairProbe results: <table border="1"> <tr><th></th><th>D</th><th>E</th><th>F</th></tr> <tr><th>A</th><td>0</td><td>1</td><td>0</td></tr> <tr><th>B</th><td>0</td><td>0</td><td>0</td></tr> <tr><th>C</th><td>0</td><td>0</td><td>0</td></tr> </table> Search the arguments of the maximum value of $M_i$ to be one forward transition (A,E) Due to the round robin behaviour of the PPLB, the interface E of $G_3$ is aligned to the next interface of A in $G_2$ . Thus we can determine the true links in the alignment by applying the offset $\alpha=-1$ to $G_3$ . $A_2 = \{ (A,D), (B,E), (C,F) \}$		D	E	F	A	0	1	0	B	0	0	0	C	0	0	0
	D	E	F															
A	0	1	0															
B	0	0	0															
C	0	0	0															
With cross traffic we know that our observation are disrupted.	Need to send $k_f$ back-to-back probe in regard of the amount of cross traffic. (we plan to determine the correct number $k_f$ in future work)	Build the forward transition matrix $M_i$ with PairProbe results: <table border="1"> <tr><th></th><th>D</th><th>E</th><th>F</th></tr> <tr><th>A</th><td>3</td><td>2</td><td>0</td></tr> <tr><th>B</th><td>1</td><td>1</td><td>4</td></tr> <tr><th>C</th><td>0</td><td>1</td><td>2</td></tr> </table> Determine one true forward transition: <ul style="list-style-type: none"> <li>• Search the arguments of one forward transition where its value is close to the mean value of <math>M_i</math>.</li> </ul> Estimate the alignment: <ul style="list-style-type: none"> <li>• Determine the offset between 2 adjacent estimated pattern.</li> </ul> $A_2 = \{ (A,D), (B,E), (C,F) \}$		D	E	F	A	3	2	0	B	1	1	4	C	0	1	2
	D	E	F															
A	3	2	0															
B	1	1	4															
C	0	1	2															

### Future work

- Validate the algorithm in a controlled environment.
- Determine the number of probes to be sent with cross traffic.
- Study PPLBs on the Internet with our algorithm.

### References

- [1] Fabien Vigier, Brice Augustin, Xavier Cuvellier, Clémence Magnien, Matthieu Latapy, Timur Friedman, and Renata Teixeira. Detection, understanding, and prevention of traceroute measurement artifacts. Elsevier, 2007.
- [2] R. Teixeira D. Veitch, B. Augustin and T. Friedman. Failure control in multipath route tracing. In INFOCOM, 2009.

This work has been funded by the European Commission FP7 project OneLab 2 and was conducted at the Université Pierre et Marie Curie in LIP6